



Sample photo

**Order symbol:** PC C 85 G  
**Product nbr:** 8724306  
**Description:** Enclosure, PC  
**Remarks:** Grey cover

**EAN:** 6418074002051  
**El. number:**  
 Finland 3423407  
 Denmark 8212001530  
 Italy 7201025  
 Sweden 2536811

**Including:** Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

Dimensions:		L	W	H	Rating:
mm:		140	80	85	<b>Ingress Protection (EN 60529):</b> IP 66/67 <b>Impact Resistance (EN 50102):</b> IK 08 <b>Electrical insulation:</b> Totally insulated <b>Halogen free (DIN/VDE 0472, Part 815):</b> Yes <b>UV resistance:</b> UL 508 <b>Flammability Rating (UL 746 C 5):</b> UL 94 5V <b>Glow Wire Test (IEC 695-2-1) °C:</b> 960 <b>NEMA Class:</b> NEMA 1, 4X, 6, 6P, 12, 13
inch:		5.5	3.1	3.3	
Materials:					
Material:		PC			
Base colour:		RAL 7035			
Cover colour:		RAL 7035			
Cover screws material:		Polyamide			
Cover screws colour:		Grey			
Gasket material:		Polyurethane			
Temperatures:					
Short term:		-40 ... 120 °C			
Continuous:		-40 ... 80 °C			
Short term:		-40 ... 250 °F			
Continuous:		-40 ... 175 °F			
Accessories:					
C-MP		Mounting plate			
CHM-3		DIN-35 Mounting rail			
FP 22040		Mounting foot kit (2 pcs)			
Certificates:					
Germanischer Lloyd (GL)					
Underwriters Laboratories					
Canadian Standards Association					
Fimko					
Europe EN 50298 1998					
UL Canada					
Gost R					

