

CABLE TIES

● LOCKING CABLE TIES



(*) Suffix "-WR" should be added if black(outdoor) color is required.

2.5 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia, (inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	DACT 80-2.3-L	80 (3.1)	2.4 (.09)	17 (.68)	8.1 (18)	MS3367-4	DAG-50	1,000
	DACT100-2.5-L	100 (4.0)		20 (.87)				
	DACT160-2.5-L	160 (6.2)	2.5 (.10)	40 (1.57)				
	DACT200-2.5-L	205 (8.0)		50 (2.00)				
3.6 TIE BODY WIDTH	DACT140-3.6-L	146 (5.7)	3.6 (.14)	35 (1.38)	17.8 (40)	MS3367-5	DAG-50	1,000
	DACT200-3.6-L	203 (8.0)		50 (2.00)				
	DACT210-3.6-L	210 (8.26)		52 (2.04)				
	DACT300-3.6-L	300 (11.8)		77 (3.03)				
	DACT370-3.6-L	370 (14.5)		102 (4.00)				

● LOCKING CABLE TIES



(*) Suffix "-WR" should be added if black(outdoor) color is required.

4.8 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia, (inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	DACT120-4.8-L	120 (4.7)	4.8 (.19)	30 (1.00)	22.2 (50)	MS3367-1	DAG-50	1,000
	DACT160-4.8-L	160 (6.2)		40 (1.57)		"		
	DACT190-4.8-L	190 (7.5)		47 (1.85)		"		
	DACT200-4.8-L	200 (8.0)		50 (2.00)		"		
	DACT250-4.8-L	250 (10.0)		64 (2.52)		"		
	DACT280-4.8-L	280 (11.0)		73 (2.87)		MS3367-7		
	DACT300-4.8-L	300 (11.8)		77 (3.03)		MS3367-7		
	DACT370-4.8-L	368 (14.5)		102 (4.00)		MS3367-2		

Material : 66 Nylon
 Color : Natural or Black(UV)
 Flammability: UL 94V-2 or UL94 V-0
 Service Temperature : 85 °C

Most **Dong-A Cable Ties**, when tested, meet the requirements of **MIL-S-23190E** (or **SAE AS23190**)

CABLE TIES

● LOCKING CABLE TIES



(*) Suffix "-WR" should be added if black(outdoor) color is required.

6.3 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia.(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	DAMCT270-6.1-L	279 (10.5)	6.1 (.24)	73 (2.87)	45.3 (100)	MS3367-3	DAG-50	100
	DAMCT300-6.3-L	300 (11.8)	6.3 (.24)	77 (3.03)				
	DAMCT370-6.3-L	370 (14.5)	6.3 (.24)	102 (4.00)				
7.6 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia.(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	DAMCT200-7.6-L	200 (8.0)	7.6 (.30)	50 (2.00)	53.4kg (120)	MS3367-3	DAG-250	100
	DAMCT300-7.6-L	300 (11.8)		77 (3.03)				
	DAMCT370-7.6-L	370 (14.5)		102 (4.00)				

● LOCKING CABLE TIES



(*) Suffix "-WR" should be added if black(outdoor) color is required.

9.0 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia.(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	DAMCT450-9.0-L	455 (17.7)	9.0 (.35)	127 (5.0)	77.8 (175)	MS3367-6	DAG-250	100
	DAMCT530-9.0-L	530 (20.9)		152 (6.0)				
	DAMCT650-9.0-L	650 (25.6)		170 (6.70)				
	DAMCT780-9.0-L	780 (30.6)		220 (9.0)				
	DAMCT880-9.0-L	880 (34.6)		260 (10.23)				
	DAMCT1000-9.0-L	1000 (42.5)		305 (12.5)				

Material : 66 Nylon
Color : Natural or Black(UV)
Flammability: UL 94V-2 or UL94 V-0
Service Temperature : 85 °C

Most **Dong-A Cable Ties**, when tested, meet the requirements of **MIL-S-23190E** (or **SAE AS23190**)