




NOTES:

- Rating: UL 45 A
IEC 41 A
PITCH: 8.00mm
- Insulation Resistance:
500MΩ or more at DC500V
- Using Temperature Range:
-40°C~+105°C
- RoHS Compliance

Normal Geometric Tolerancing			
—	//	≡	⊥
0 to 100	0.2	0 to 10	0.2
over 100 to 150	0.3	over 10	0.3
over 150	0.5		
Total Pitch Tolerances		Normal dimension Tolerances	
0<U<=30	±0.20	0~30	±0.25
30<U<=53	±0.25	over 30~53	±0.30
53<U<=70	±0.30	over 53~70	±0.35
70<U<=90	±0.35	over 70~90	±0.44
90<U<=115	±0.44	over 90~115	±0.55

P	2	3	4	5	6
U	8.00	16.00	24.00	32.00	40.00
V	14.50	22.50	30.50	38.50	46.50
P	7	8	9	10	
U	48.00	56.00	64.00	72.00	
V	54.50	62.50	70.50	78.50	

包射的金属材料		COPPER ALLOY	Tin Plated
1	MOLDING PLASTIC	PA66	UL94-V0 GREY
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	W K	DATE	11.06.23	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	4:1 (:)		 
APP.		DATE		NAME	CSC-6XXPS		
 DINKLE				DWG NO.	SP-03-CSC6XXPS		
DINKLE ENTERPRISE CO.,LTD							