本公司智慧財產，未經同意不得複製
Diptronics copyright,
may not be used without permission from Diptronics.



RBH3-16R



RBH3-10R



NOTE:
1.GENERAL TOLERANCES MAX.±0.20mm.

SPECIFICATIONS
1.RATING : NON SWITCHING RATING 24VDC 400mA
SWITCHING RATING 24VDC 150mA
2.LIFF : 10,000 STEPS
3.OPERATING FORCE : 400gf·cm Max.
4.INITIAL CONTACT RESISTANCE : 100mOhm Max.
5.DIELECTRIC STRENGTH : AC 250V 1 MINUTE
6.INSULATION RESISTANCE : 100MOhm Min.
(DC 250V MEGGER)
7.OPERATING TEMPERATURE : −60°C TO 125°C





P.C.B. LAYOUT

TYPE	CIRCUIT CHARACTERISTICS															
RBH3-10R	CODE	POSITION ●ON														
		0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
	1		●		●		●		●		●						
	2			●	●			●	●								
	4					●	●	●	●								
	8									●	●						

TYPE	CIRCUIT CHARACTERISTICS															
RBH3-16R	CODE	POSITION ●ON														
		0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
	1		●		●		●		●		●		●		●		●
	2			●	●			●	●			●	●			●	●
	4					●	●	●	●					●	●	●	●
	8									●	●	●	●	●	●	●	●

DIPTRONICS 圜達 2014. AUG.14 ISSUED R&D DEPT

ZONE	REV.	DESCRIPTION	DATE	APPD.
	A	DWG REL.	2014.07.14	邱明義

APPD: 邱明義	Q'TY:	圜達實業股份有限公司 DIPTRONICS MANUFACTURING INC.	PART NAME: ROTARY SWITCH
CHKD: 邱明義	SCALE: 5:1		
DR: LARRY	REV: A UNITS: mm	PART NO: RBH3-1□RAV□ MAT'L:	DWG NO: RD12PBA
DESIGN: LARRY		FINISH:	