




JIANGSU CHANGJIANG ELECTRONICS TECHNOLOGY CO., LTD

## SOD-323 Plastic-Encapsulate Diode

**1SS380**    Switching Diodes**FEATURES**

- Small surface mounting type.
- High speed.
- Suitable for high packing density.



MAKING:6D

**Maximum Ratings and Electrical Characteristics, Single Diode @T<sub>A</sub>=25°C**

Parameter	Symbol	Limits		Unit
Peak reverse voltage	V <sub>RM</sub>	40		V
DC reverse voltage	V <sub>R</sub>	35		V
Mean rectifying current	I <sub>O</sub>	0.1		A
Peak forward surge current	I <sub>FSM</sub>	0.225		A
Junction temperature	T <sub>j</sub>	125		°C
Storage temperature	T <sub>stg</sub>	-55~+125		°C

**Electrical Ratings @T<sub>A</sub>=25°C**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	V <sub>F</sub>			1.2	V	I <sub>F</sub> =100mA
Reverse current	I <sub>R</sub>			15	nA	V <sub>R</sub> =20V
Capacitance between terminals	C <sub>T</sub>			5	pF	V <sub>R</sub> =0.5V,f=1MHZ