



SPECIFICATION

DESCRIPTION	SLIDE SWITCH	DATE	APR. 13, 98	WRT'T	CHK'D	APP'D
MODEL NO.	1250	PAGE	1 OF 1	<i>Hyang</i>		

1. RATING

- 1.1 RATING : DC 6V 0.3A
- 1.2 CIRCUIT : 1C-2P
- 1.3 TIMING : NON-SHORTING
- 1.4 CONTACT RESISTANCE : 70mΩ MAX
- 1.5 OPERATING FORCE : 200±100gf
- 1.6 STROKE : 2mm

2. ELECTRICAL SPECIFICATION

2.1 CONTACT RESISTANCE

SHALL BE MEASURED AT 1KHZ / MAX.20mV OR 1A / 5V DC BY A VOLTAGE DROP METHOD.

LESS THAN 70mΩ.

2.2 INSULATION RESISTANCE

SHALL BE MEASURED BY APPLYING 100V DC BETWEEN ALL TERMINALS AND BETWEEN THE TERMINAL FOR 1 MINUTE.

MORE THAN 100MΩ.

2.3 WITHSTAND VOLTAGE

100V AC / 2mA SHALL BE APPLIED BETWEEN ALL TERMINALS AND BETWEEN THE TERMINAL FOR 1 MINUTE.

SHALL BE FREE FROM DIELECTRIC BREAKAGE.

3. DURABILITY

10,000 CYCLES OF OPERATION SHALL BE PERFORMED CONTINUOUSLY AT A RATE OF 15~20 CYCLES / MINUTE WITHOUT LOAD.

4. SOLERABILITY

THE TEST SHALL BE CONDUCTED UNDER THE FOLLOWING CONDITIONS AND CONFIRMED AFTER THAT :

SOLERING TEMPERATURE : 230±5℃

IMMERSING TIME : 3±0.5 SEC.