

Spezifikation für Freigabe / specification for release

Kunde / customer : _____

Artikelnummer / part number : **74271132**

Bezeichnung : **STAR-TEC mit Sicherheitsverschuß**

description : **STAR-TEC with Safety Lock**



DATUM / DATE : 2008-01-03

A Mechanische Abmessungen / dimensions:

	a	24,5 typ.	mm
	b	40,5 typ.	mm
	c	21,0 typ.	mm
	für Kabeldurchmesser / for cable diameter		
	Ø	7 - 8,5	mm

B Elektrische Eigenschaften / electrical properties:

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	Tol.
Impedanz @ 1 Wg./ impedance @ 1 turn	25 MHz	Z	141	Ω	± 25%
Impedanz @ 1 Wg./ impedance @ 1 turn	100 MHz	Z	241	Ω	± 25%
Impedanz @ 2 Wg./ impedance @ 2 turn	25 MHz	Z	603	Ω	typ.
Impedanz @ 2 Wg./ impedance @ 2 turn	100 MHz	Z	755	Ω	typ.

C



D Prüfgeräte / test equipment:

HP 4191 B für/for Z und/and material
16092A - Klemme / clamp
AWG26 - Ø 0,5mm - Länge/length: 165 mm

E Testbedingungen / test conditions:

Luftfeuchtigkeit / humidity: 33%
 Umgebungstemperatur / temperature: + 20°C

F Werkstoffe & Zulassungen / material & approvals:

Basismaterial / base material: 4 W 620
 Kunststoff / plastic material: PA 66 / 6
 UL-Zulassungen / UL-approval: UL94-V0 / E53898
 Farbe / colour: elektrograu / electronic grey

G Eigenschaften / general specifications:

Curietemperatur / curie temperature: + 150°C
 Gewicht / weight: 34,0g typ.
 Lagertemperatur / storage temperature: -40°C ~ + 85°C
 Betriebstemp. / operating temperature: -25°C ~ +105°C

Freigabe erteilt / general release:	Kunde / customer				
Datum / date	Unterschrift / signature		SMU	Version 6	08-01-03
			SMU	Version 5	07-01-22
	Würth Elektronik		AF	Version 4	06-11-13
			SMU	Version 3	06-11-13
			LF	Version 2	04-10-11
			JH	Version 1	00-12-06
Geprüft / checked	Kontrolliert / approved		Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>

Spezifikation für Freigabe / specification for release

Kunde / customer : _____

Artikelnummer / part number : **74271132**




Bezeichnung : **STAR-TEC mit Sicherheitsverschluß**

description : **STAR-TEC with Safety Lock**

DATUM / DATE : 2008-01-03

H Impedanzverlauf / impedance curve:



A: 2 x durch Bohrung Ferrit / 2 x times through ferrite

B: 1 x durch Bohrung Ferrit / 1 x times trough ferrite

Freigabe erteilt / general release:	Kunde / customer				
.....			SMU	Version 6	08-01-03
			SMU	Version 5	07-01-22
Datum / date	Unterschrift / signature		AF	Version 4	06-11-13
.....	Würth Elektronik		SMU	Version 3	06-11-13
			LF	Version 2	04-10-11
.....			JH	Version 1	00-12-06
	Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400

<http://www.we-online.com>

SEITE 2 VON 2