

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

744045102


Bezeichnung : SMD HF-Drossel WE-LQ

description : SMD HF-CHOKE WE-LQ



DATUM / DATE : 2008-10-31

A Mechanische Abmessungen / dimensions:




	Typ L	
A	4,5 ± 0,3	mm
B	3,2 ± 0,3	mm
C	2,6 ± 0,3	mm
D	3,6 ± 0,3	mm
E	1,6 ref	mm
F	1,3 ref	mm
G	5,4 ref	mm
H	3,6 ref	mm

Marking = Inductance code

C Lötpad / soldering spec.:

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Induktivität / inductance	1 kHz / 1V	L	1000,00	µH	± 10%
Güte Q / Q factor	252 kHz	Q	28		ref.
DC-Widerstand / DC-resistance	@ 20°C	R _{DC}	30,000	Ω	max.
Nennstrom / rated current	ΔT= 40 K	I _{DC}	0,070	A	max.
Sättigungsstrom / saturation current	ΔL/L <10%	I _{sat}	0,160	A	min.
Eigenres.-Frequenz / self-res.-frequency		SRF	2	MHz	min.



D Prüfgeräte / test equipment:

HP 4274 A für/for L und/and Q

HP 34401 A für/for R_{DC} und I_{DC}

E Testbedingungen / test conditions:

Luftfeuchtigkeit / humidity: 33%
Umgebungstemperatur / temperature: +20°C

F Werkstoffe & Zulassungen / material & approvals:

Basismaterial / base material: Ferrit
Draht / wire: Class F
Pin / Terminal: Sn/Cu - 99,3/0,7%

G Eigenschaften / general specifications:

Betriebstemp. / operating temperature: -40°C - + 125°C
Umgebungstemp. / ambient temperature: -40°C - + 85°C
It is recommended that the temperature of the part does not exceed 125°C under worst case operating conditions.

Freigabe erteilt / general release:	Kunde / customer			
Datum / date	Unterschrift / signature			
	Würth Elektronik	SSt	Version 4	08-10-31
		UB	Version 3	06-07-14
		SST	Version 1	05-08-03
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co.KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
http://www.we-online.com

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number : 744045102

Bezeichnung : SMD HF-Drossel WE-LQ


description : SMD HF-CHOKE WE-LQ



DATUM / DATE : 2008-10-31

H Induktivitätskurve / Inductance curve :

Induktivität vs Strom (typ.) /
Inductance vs Current (typ.)



Freigabe erteilt / general release:	Kunde / customer			
Datum / date	Unterschrift / signature			
	Würth Elektronik	SSt	Version 4	08-10-31
		UB	Version 3	06-07-14
		SST	Version 1	05-08-03
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co.KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
http://www.we-online.com

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

744045102

Bezeichnung : SMD HF-Drossel WE-LQ

description : SMD HF-CHOKE WE-LQ





DATUM / DATE : 2008-10-31

I Rollenspezifikation / tape and reel specification:


Gurtspezifikation / Tape specification:

A	$8,0 \pm 1,0$	mm
B	$4,0 \pm 0,1$	mm



Rollenspezifikation / Reel specification:

a	$178 \pm 0,5$	mm
b	$20,20 \pm 0,1$	mm
c	$13,00^{+0,5}_{-1,0}$	mm
d	$50,0 \pm 1,0$	mm



The force for tearing off cover tape is
20 to 70 grams in arrow direction

Freigabe erteilt / general release:

Kunde / customer

Datum / date

Unterschrift / signature

Würth Elektronik

Geprüft / checked

Kontrolliert / approved

SSt	Version 4	08-10-31
UB	Version 3	06-07-14
SST	Version 1	05-08-03
Name	Änderung / modification	Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance

Würth Elektronik eiSos GmbH & Co.KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>