

2011.11.17

MB-RD-E11117-03

SPECIFICATIONS SHEET

**WLAN ANTENNA
(PE11x)**

CONFIDENTIAL

This Document contains confidential and proprietary information,
cannot discourse to third party without the prior written Authorization of Mobinus

1. General Application

This document specifies the chip antenna for the mobile communication terminal.

Model Number	PE11x
Application	WiFi, BT

2. Technical Specification

2.1 Electrical Specification


No	Item	Specification	Remarks
1	Frequency Range	2.4GHz ~ 2.5GHz	
2	VSWR	2.0: 1	
3	Impedance	50 Ω	
4	3D Efficiency	74%	Test Jig
5	Polarization	Linear	
6	Radiation Pattern	Omni directional	

2.2 Mechanical Specification


No	Item	Specification	Remarks
1	Dimension	4 * 10 * 2.0(H)mm	
2	Radiator Material	Copper	
3	Operating Temperature	-30℃ ~ +80℃	
4	Operating Humidity	10% ~ 90%	
5	Weight	N/A	
6	Connector Type	Solder(SMT)	

3. Measurement Data

3.1 VSWR & Smith Chart



< Smith Chart >



< VSWR >

Fig 2. VSWR & Smith Chart

3.2 Test Result (3D Efficiency)

	1	2	3	4	5	6	7	8	9	10	11
Frequency(MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Efficiency(dB)	-1.27	-1.06	-1.14	-1.21	-1.16	-1.34	-1.57	-1.23	-1.24	-1.27	-1.48
Efficiency(%)	74.63	78.42	76.94	75.63	76.54	73.42	69.60	75.38	75.12	74.71	71.20
TRG(dB)	-1.27	-1.06	-1.14	-1.21	-1.16	-1.34	-1.57	-1.23	-1.24	-1.27	-1.48
TRG _{Thata} (dB)	-1.56	-1.35	-1.44	-1.52	-1.49	-1.67	-1.91	-1.55	-1.58	-1.59	-1.81
TRG _{Phi} (dB)	-13.24	-12.93	-12.88	-12.84	-12.55	-12.70	-12.85	-12.62	-12.55	-12.64	-12.72
UHRG(dB)	-7.13	-6.96	-7.07	-7.15	-7.10	-7.29	-7.51	-7.18	-7.23	-7.32	-7.59
UHRG/TRG(%)	25.97	25.67	25.49	25.46	25.45	25.43	25.46	25.42	25.22	24.80	24.46
H-Plane	-0.17	0.03	-0.06	-0.12	-0.08	-0.27	-0.51	-0.16	-0.22	-0.33	-0.66
E1-Plane, AVG(dB)	-1.00	-0.77	-0.85	-0.90	-0.81	-0.95	-1.18	-0.82	-0.83	-0.83	-1.03
E2-Plane, AVG(dB)	-3.30	-3.09	-3.17	-3.25	-3.23	-3.47	-3.74	-3.42	-3.46	-3.49	-3.73
Peak Gain(dB)	3.60	3.84	3.81	3.83	3.98	3.86	3.68	4.07	4.08	4.11	3.98
Directivity(dB)	4.88	4.90	4.95	5.05	5.14	5.20	5.25	5.30	5.33	5.38	5.45
Minimum Gain(dB)	-16.81	-18.12	-19.51	-19.69	-18.41	-18.23	-18.02	-17.31	-16.61	-15.73	-15.06
Test Condition	FS										
Antenna Type											
Average Efficiency	-1.27 dB, 74.69 %										

3.3 Radiation Pattern





Fig 3. Radiation Pattern


4. Application Guide

4.1 PCB Design Guide



	A	B	C	D	L	W
길이(mm)	1.7	1.7	2.0	3.0	10.4	4.4

4.2 Default Condition Matching Circuit



Z1	5.6nH
Z2	3.3nH
Z3	DNI

< Default Matching Value >