

UV Radiometer 1.0

GUVx-T1xGS-LA5



Description

It inform the UV power of UV source through the LCD using UV Sensor. You can choose the sensor part by your application.

Constitution

Display, Adapter, Sensor Probe, Connection Cable, Output Line




Fig. 1 Picture and Drawing of UV Radiometer 1.0

Case dimensions

Type	Width (mm)	Length (mm)	Height (mm)	Window (mm)	Weight (g)	Connection Line (m)	Body	Remark
Display	88	137	30	-	155	-	-	
Probe	30	36	16	12	40	5	Al-60	

Information of UV Radiometer

Parameter		Value			Unit	Remark
		Min.	Typ.	Max.		
Operating Temperature		-15		65	℃	
Power Consumption			0.13		A	
Detection Range	GUVV-T10GS-LA5	230		395	nm	10% of Max
	GUVB-T11GS-LA5	220		320	nm	10% of Max
	GUVC-T10GS-LA5	220		280	nm	10% of Max

Connection

1. Main Power
 - DC 9V 300 mA (AC220V 50/60 Hz Adapter)
2. Detection Power Range
 - Standard : Max. 100 mW/cm²
 - Option : Max. 10 mW/cm² , Max. 1000 mW/cm²
3. Output
 - It depends on UV power of UV source.
 - 1) Voltage : 0 ~ 5 V, 0.1A Max.
 - 2) Current : 4 ~ 20 mA, 5V

LCD Display

[MODE : UVA R.P.]

[DATA : 100 %]

1st Line : Sensor Type & Function

1) Sensor Type : UVV/UVA/UVB/UVC

2) Function : Using Mode Button

- A.P. : Absolute Power (unit : mW/cm²)

- R.P. : Relative Power (unit : %)

- Time : Cumulative Time

2nd Line : Data According To The Each Functions