No. of Contacts	DIME NSIONS	
	A	B
2	2.00	4.00
3	4.00	6.00
4	6.00	8.00
5	8.00	10.00
6	10.00	12.00
7	12.00	14.00
8	14.00	16.00
9	16.00	18.00
10	18.00	20.00
11	20.00	22.00
12	22.00	24.00
13	24.00	26.00
14	26.00	28.00
15	28.00	30.00
16	30.00	32.00
17	32.00	34.00
18	34.00	36.00
19	36.00	38.00
20	38.00	40.00
21	40.00	42.00
22	42.00	44.00
23	44.00	46.00
24	46.00	48.00
25	48.00	50.00
26	50.00	52.00
27	52.00	54.00
28	54.00	56.00
29	56.00	58.00
30	58.00	60.00
31	60.00	62.00
32	62.00	64.00
33	64.00	66.00
34	66.00	68.00
35	68.00	70.00
36	70.00	72.00
37	72.00	74.00
38	74.00	76.00
39	76.00	78.00
40	78.00	80.00







SPECIFICATIONS

Current Rating: 1.5Amps
Insulation Resistance: 1000MΩ Min
Contact Resistance: 20MΩ Max
Withstanding Voltage: AC 500V
Operation Temperature:-40°to+ 105°
Contact Material: Brass
Insrlator Material: Polyester(UL 94V-0)
Standard: PA46
Max.Processing Temp:
240° C for30-60seconds
(260° C for10seconds)



Recommended P.C.B Hole Layout

检测以此为准

UNLESS OTHEWIXE SPECIFIED TOLERANCE			
x.	±0.3	x.°	±5°
x.x	±0.2	x.x°	±1°
x.xx	±0.1	x.xx°	±0.5°
SCALE		UNIT	mm
DRAWN	LI BEI LIN		18/01/08
CHECKED			
APPROVED		/	/
SIZE	A4	REV	A

DRAWM NAME: 2.0mm Female Header

PROUCT NO.

PILE NAME:

2.0PF 2*NPin H7.2 90° PC2.8