



Sample photo

**Order symbol:** ABS 150/75 LT  
**Product nbr:** 6082915  
**Description:** Enclosure, ABS  
**Remarks:** Smoked transparent cover

**EAN:** 6418074023155  
**El. number:**  
 Finland 3420625  
 Denmark 8212023547  
 Italy 7362080  
 Sweden 2535845

**Including:** Base with TPE gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:		L	W	H	Rating:
mm:		180	130	75	<b>Ingress Protection (EN 60529):</b> IP 66/67 <b>Impact Resistance (EN 50102):</b> IK 07 <b>Electrical insulation:</b> Totally insulated <b>Halogen free (DIN/VDE 0472, Part 815):</b> Yes <b>Flammability Rating (UL 746 C 5):</b> UL 94 HB <b>Glow Wire Test (IEC 695-2-1) °C:</b> 650 <b>NEMA Class:</b> NEMA 1, 4, 4X, 6
inch:		7.1	5.1	3	
Materials:					
Material:		ABS			<b>Certificates:</b>  Fimko Europe EN 50298 1998 Gost R
Base colour:		RAL 7035			
Cover colour:		Smoked grey			
Cover screws material:		Polyamide			
Cover screws colour:		Black			
Gasket material:		TPE			
Temperatures:					
Short term:		-40 ... 80 °C			
Continuous:		-40 ... 60 °C			
Short term:		-40 ... 175 °F			
Continuous:		-40 ... 140 °F			
Accessories:					
MIV 150		Mounting plate			
MIN 10		DIN-15 Mounting rail			
MIN 15		DIN-15 Mounting rail			
MIV 10		DIN-35 Mounting rail			
MIV 15		DIN-35 Mounting rail			
FP A 150/180		Front plate			
HFP 180		Front plate hinge series			

