



Sample photo

Order symbol: ABS 150/75 HT
Product nbr: 6081914
Description: Enclosure, ABS
Remarks: Smoked transparent cover

EAN: 6418074023186
El. number:
 Finland 3420633
 Denmark 8212023576
 Italy 7362095
 Sweden 2535854

Including: Base with TPE gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:		L	W	H	Rating:
mm:		180	130	75	Ingress Protection (EN 60529): IP 66/67
inch:		7.1	5.1	3	Impact Resistance (EN 50102): IK 07
Materials:					Electrical insulation: Totally insulated
Material:		ABS			Halogen free (DIN/VDE 0472, Part 815): Yes
Base colour:		RAL 7035			Flammability Rating (UL 746 C 5): UL 94 HB
Cover colour:		Smoked grey			Glow Wire Test (IEC 695-2-1) °C: 650
Cover screws material:		Polyamide			NEMA Class: NEMA 1, 4, 4X, 6
Cover screws colour:		Black			Certificates:
Gasket material:		TPE			
Temperatures:					Europe EN 50298 1998
Short term:		-40 ... 80 °C			Gost R
Continuous:		-40 ... 60 °C			
Short term:		-40 ... 175 °F			
Continuous:		-40 ... 140 °F			
Accessories:					
MIV 150		Mounting plate			
MIN 10		DIN-15 Mounting rail			
MIN 15		DIN-15 Mounting rail			
MIV 10		DIN-35 Mounting rail			
MIV 15		DIN-35 Mounting rail			
FP A 150/180		Front plate			
HFP 180		Front plate hinge series			

