



REV.	DATE	MODIFICATION	APPROVER
A	09.06.01	NEW	Vicky
B	12.03.12		Vicky
C			





USE GUIDE















SPECIFCATIONS:

1. CURRENT RATING: 0.5A 50V AC/DC.
2. CONTACT RESISTANCE: 60mΩ MAX AT DC 20mA.
3. INSULATION RESISTANCE: 100MΩ MIN AT 500V DC.
4. OPERATION TEMPERATURE RANGE: -25℃ TO+85℃
5. HOUSING: PA9T+30%GF UL94V-0 BLACK
6. TEMINAL: CuBe290-TM04 T=0.10mm, GLOD 8u"PLATED
7. GROUND SLICE: BRASS (C2680R-H) T=0.20mm, TIN PLATED
8. GO TO SLICE: BRASS (C2680R-H) T=0.30mm, TIN PLATED



GENERAL TOLERANCE			
SELECT	✓		
TOL. / ON.	1	2	3
X. XXX ±		0.05	0.15
X. XX ±	0.10	0.13	0.25
X. X ±	0.20	0.25	0.5
X. ±		0.38	1.00
ANGLE ±	1°		

UNITS	mm
MAT'L	NONE
FINISH	NONE
Q'TY	NONE

NAME	
PART NO:	ATOM010020010033
APPD:	Vicky
CHKD:	Ivy
DR:	Linda
TITLE:	BATTERY 2.5mm 3P H=3.5mm SMT 沉板式
DWG NO.	BATTERY

SCALE	SHEET	REV
1:1	1 OF 1	B