





P.C.B LAYOUT
TOP VIEW



SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: d0.03Ω;
3. Insulation resistance: e100MΩ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. life test: 5,000 cycles。

SCHEMATIC



NO.	DESCRIPTION	QTY	MATERIAL	PLATING
6	HOUSING	1	PBT	
5	5# CONTACT FOOT	1	SUS301 T=0.2	Ni??-Sn-Plating
4	4# CONTACT FOOT	1	H62 BRASS T=0.4	Ni??-Sn-Plating
3	3# CONTACT FOOT	1	H62 BRASS T=0.4	Ni??-Sn-Plating
2	2# CONTACT FOOT	1	SUS301 T=0.2	Ni??-Sn-Plating
1	1# CONTACT FOOT	1	PHOSPHOR BRONZE T=0.25	Ni??-Sn-Plating

UNIT: MM	TYPE:	MODEL NO:	PAPER NO: A4		PAGE 1 OF 1	
	PHONE JACK	PJ-3007C-X	TOLERANCE	ANGLES	SCALE	VER
			0.15	氨1.5	3:1	1

DESIGNER BY:	
CHECK BY:	
APPROVED BY:	

Green Electronics CO,.LTD

GREEN ELECTRONICS COMPANY Tel 0755-8