




P.C.B LAYOUT
TOP VIEW



SCHEMATIC



SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: ⩽0.03Ω;
3. Insulation resistance: ⩾100MΩ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. life test: 5,000 cycles。

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
5	AXIS SUPPORT	1	H59 BRASS	Ni-Plating
4	CURVE PIECE	1	H62 BRASS	Sn-Plating
3	SPRING PIECE	1	PHOSPHOR BRONZE	Sn-Plating
2	CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
1	HOUSING	1	PBT/PA66	

UNIT: MM	TYPE:	MODEL NO:	PAPER NO: A4		PAGE 1 OF 1	
	PHONE JACK	PJ-319	TOLERANCE	ANGLES	SCALE	VER
			±0.15	±1.5°	3:1	1

DESIGNER BY:	
CHECK BY:	
APPROVED BY:	

Green Electronics CO,.LTD

GREEN ELECTRONICS COMPANY Tel 0766[illegible]796