




PJ-325D	PJ-325D-1	PJ-325D-2	PJ-325D-3	PJ-325D-4


## SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance:  $\leq 0.03 \Omega$ ;
3. Insulation resistance:  $\geq 100M \Omega$  (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. life test; 5,000 cycles.



7	COVER	1	PBT	
6	HOUSING	1	PBT/PC	
5	SPRING PIECE	1	PHOSPHOR BRONZE	Sn-Plating
4	CURVE PIECE	1	H62 BRASS	Sn-Plating
3	SPRING PIECE	1	PHOSPHOR BRONZE	Sn-Plating
2	CURVE PIECE	1	H62 BRASS	Sn-Plating
1	FLAT PIECE	1	H62 BRASS	Sn-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

	UNIT:MM	TYPE:	MODEL NO:	PAPER NO: A4	PAGE 1 OF 1		
		PHONE JACK	PJ-325D	TOLERANCE	ANGLES	SCALE	YES
				0.16	1:1.5	8:1	1

DESIGNER	
CHECK BY:	
APPROVED BY:	

Green Electronics CO.,LTD





## SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance:  $\leq 0.03 \Omega$ ;
3. Insulation resistance:  $\geq 100 M\Omega$  (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. life test: 5,000 cycles.



7	COVER	1	PBT	
6	HOUSING	1	PBT/PC	
5	SPRING PIECE	1	PHOSPHOR BRONZE	Sn-Plating
4				
3	SPRING PIECE	1	PHOSPHOR BRONZE	Sn-Plating
2				
1	FLAT PTECE	1	H62 BRASS	Sn-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

	TYPE: PHONE JACK	MODEL NO: PJ-325D-2	PAPER NO: A4	SCALE 1 OF 1		
			TOLERANCE	ANGLES	CAGE	YER
			0.15	0.15	3:1	1

DESIGNER	
By: 	
CHECK BY:	
APPROVED BY:	

Green Electronics CO.,LTD