




P.C.B LAYOUT
TOP VIEW



SCHEMATIC



SPECIFICATION

1. Rating : DC 30V 1.0A;
2. Contact resistance: d0.03Ω;
3. Insulation resistance: e100MΩ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 5-30N;
6. life test: 5,000 cycles。

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
12	AXIS SUPPORT	1	H59 BRASS	Au(Ni)-Plating
11	COVER	1	ABS	
10	HOUSING	1	ABS	
9	CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
8	SPRING	1	PHOSPHOR BRONZE	Sn-Plating
7	FLAT PIECE	1	BRASS	Sn-Plating
6	CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
5	SPRING	1	PHOSPHOR BRONZE	Sn-Plating
4	FLAT PIECE	1	BRASS	Sn-Plating
3	CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
2	CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
1	CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating

UNIT: MM	TYPE:	MODEL NO:	PAPER NO: A4		PAGE 1 OF 1	
	PHONE JACK	PJ-604A	TOLERANCE	ANGLES	SCALE	VER
			0.15	≤1.5	2:1	1

DESIGNER BY:	
CHECK BY:	
APPROVED BY:	

Green Electronics CO,.LTD

GREEN ELECTRONIC COMPANY Tel:0769-8796