
- **Monolithic Silicon IC Containing Photodiode, Operational Amplifier, and Feedback Components**
- **Converts Light Intensity to a Voltage**
- **High Irradiance Responsivity, Typically 137 mV/(μW/cm^2) at λ_p = 635 nm (TSL250R)**
- **Compact 3-Lead Clear Plastic Package**
- **Single Voltage Supply Operation**
- **Low Dark (Offset) Voltage....10mV Max**
- **Low Supply Current.....1.1 mA Typical**
- **Wide Supply-Voltage Range.... 2.7 V to 5.5 V**
- **Replacements for TSL250, TSL251, and TSL252**


PACKAGE
(FRONT VIEW)



Description

The TSL250R, TSL251R, and TSL252R are light-to-voltage optical sensors, each combining a photodiode and a transimpedance amplifier (feedback resistor = 16 MΩ, 8 MΩ, and 2.8 MΩ respectively) on a single monolithic IC. Output voltage is directly proportional to the light intensity (irradiance) on the photodiode. These devices have improved amplifier offset-voltage stability and low power consumption and are supplied in a 3-lead clear plastic sidelooker package with an integral lens

Functional Block Diagram



Terminal Functions

TERMINAL NAME	TERMINAL NO.	DESCRIPTION
GND	1	Ground (substrate). All voltages are referenced to GND.
OUT	3	Output voltage
V_{DD}	2	Supply voltage

Copyright © 2001, TAOS Inc.

Texas Advanced Optoelectronic Solutions Inc.
800 Jupiter Road, Suite 205 • Plano, TX 75074 • (972) 673-0759

Absolute Maximum Ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage, V_{DD} (see Note 1) . . . . . 6 V
Output current, I_O . . . . . ±10 mA
Duration of short-circuit current at (or below) 25°C (see Note 2) . . . . . 5 s
Operating free-air temperature range, T_A . . . . . –25°C to 85°C
Storage temperature range, T_{stg} . . . . . –25°C to 85°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds . . . . . 240°C

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltages are with respect to GND.
2. Output may be shorted to supply.

Recommended Operating Conditions

	MIN	NOM	MAX	UNIT
Supply voltage, V_{DD}	2.7		5.5	V
Operating free-air temperature, T_A	0		70	°C

Electrical Characteristics at V_{DD} = 5 V, T_A = 25°C, λp = 635 nm, R_L = 10 kΩ (unless otherwise noted) (see Notes 3, 4, and 5)

PARAMETER		TEST CONDITIONS	TSL250R			TSL251R			TSL252R			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
V_D	Dark voltage	E_e = 0	0	4	10	0	4	10	0	4	10	mV
V_{OM}	Maximum output voltage	V_{DD} = 4.5 V	3.0	3.3		3.0	3.3		3.0	3.3		V
V_O	Output voltage	E_e = 14.6 μW/cm²	1.5	2	2.5							V
		E_e = 38.5 μW/cm²				1.5	2	2.5				
		E_e = 196 μW/cm²							1.5	2	2.5	
α_{vo}	Temperature coefficient of output voltage (V_O)	E_e = 14.6 μW/cm², T_A = 0°C to 70°C		1.6								mV/°C
				0.08								%/°C
		E_e = 38.5 μW/cm², T_A = 0°C to 70°C					1.6					mV/°C
							0.08					%/°C
		E_e = 196 μW/cm², T_A = 0°C to 70°C								1.6		mV/°C
										0.08		%/°C
N_e	Irradiance responsivity	λ_p = 635 nm, See Notes 5 and 7		137			52			10.2		mV/(μW/cm²)
		λ_p = 880 nm, See Notes 6 and 7		127			48			9.4		
I_{DD}	Supply current	E_e = 14.6 μW/cm²		1.1	1.7							mA
		E_e = 38.5 μW/cm²					1.1	1.7				
		E_e = 196 μW/cm²								1.1	1.7	


NOTES: 3. Measurements are made with R_L = 10 kΩ between output and ground.
4. Optical measurements are made using small-angle incident radiation from an LED optical source.
5. The input irradiance E_e is supplied by an AlInGaP LED with peak wavelength λ_p = 635 nm
6. The input irradiance E_e is supplied by a GaAlAs LED with peak wavelength λ_p = 880 nm
7. Irradiance responsivity is characterized over the range V_O = 0.05 to 2.9 V. The best-fit straight line of Output Voltage V_O versus irradiance E_e over this range will typically have a positive extrapolated V_O value for E_e = 0.

Copyright © 2001, TAOS Inc.

Dynamic Characteristics at T_A = 25°C (see Figure 1)

PARAMETER		TEST CONDITIONS	TSL250R			TSL251R			TSL252R			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
t_r	Output pulse rise time	V_{DD} = 5 V, λ_p = 635 nm		260			70			7		µs
t_f	Output pulse fall time	V_{DD} = 5 V, λ_p = 635 nm		260			70			7		µs
V_n	Output noise voltage	V_{DD} = 5 V, E_e = 0, f = 1000 Hz		0.8			0.7			0.6		µV/√Hz

PARAMETER MEASUREMENT INFORMATION



TEST CIRCUIT **VOLTAGE WAVEFORM**

NOTES: A. The input irradiance is supplied by a pulsed AlInGaP light-emitting diode with the following characteristics: λ_p = 635 nm, t_r < 1 µs, t_f < 1 µs.

B. The output waveform is monitored on an oscilloscope with the following characteristics: t_r < 100 ns, $Z_i \geq 1$ MΩ, $C_i \leq 20$ pF.

Figure 1. Switching Times

Copyright © 2001, TAOS Inc.

TYPICAL CHARACTERISTICS

OUTPUT VOLTAGE vs IRRADIANCE




Figure 2

PHOTODIODE SPECTRAL RESPONSIVITY




Figure 3

MAXIMUM OUTPUT VOLTAGE vs SUPPLY VOLTAGE




Figure 4

SUPPLY CURRENT vs OUTPUT VOLTAGE




Figure 5

Copyright © 2001, TAOS Inc.

TYPICAL CHARACTERISTICS




Figure 6

Copyright © 2001, TAOS Inc.

MECHANICAL INFORMATION

The device is supplied in a clear plastic three-lead package. The integrated photodiode active area is typically 1,0 mm^2 (0.0016 in^2) for TSL250R, 0,5 mm^2 (0.00078 in^2) for the TSL251R, and 0,26 mm^2 (0.0004 in^2) for the TSL252R.




Figure 7. Package Configuration

NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. All dimensions apply before solder dip.
D. Package body is a clear nonfilled optically transparent material
E. Index of refraction of clear plastic is 1.55.

Copyright © 2001, TAOS Inc.

PRODUCTION DATA — information in this document is current at publication date. Products conform to specifications in accordance with the terms of Texas Advanced Optoelectronic Solutions, Inc. standard warranty. Production processing does not necessarily include testing of all parameters.

NOTICE

Texas Advanced Optoelectronic Solutions, Inc. (TAOS) reserves the right to make changes to the products contained in this document to improve performance or for any other purpose, or to discontinue them without notice. Customers are advised to contact TAOS to obtain the latest product information before placing orders or designing TAOS products into systems.

TAOS assumes no responsibility for the use of any products or circuits described in this document or customer product design, conveys no license, either expressed or implied, under any patent or other right, and makes no representation that the circuits are free of patent infringement. TAOS further makes no claim as to the suitability of its products for any particular purpose, nor does TAOS assume any liability arising out of the use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages.

TEXAS ADVANCED OPTOELECTRONIC SOLUTIONS, INC. PRODUCTS ARE NOT DESIGNED OR INTENDED FOR USE IN CRITICAL APPLICATIONS IN WHICH THE FAILURE OR MALFUNCTION OF THE TAOS PRODUCT MAY RESULT IN PERSONAL INJURY OR DEATH. USE OF TAOS PRODUCTS IN LIFE SUPPORT SYSTEMS IS EXPRESSLY UNAUTHORIZED AND ANY SUCH USE BY A CUSTOMER IS COMPLETELY AT THE CUSTOMER'S RISK.

TAOS, the TAOS logo, and Texas Advanced Optoelectronic Solutions are trademarks of Texas Advanced Optoelectronic Solutions Incorporated.

Copyright © 2001, TAOS Inc.

Copyright © 2001, TAOS Inc.