

## Rated Power:

The maximum value of power which can be continuously loaded to a resistor at a rated ambient temperature.

## Rated Voltage:

The maximum value of D.C. voltage or A.C. voltage (rms) capable of being applied continuously to a resistor at the rated ambient temperature. Rated voltage shall be calculated from the following formula:

Rated Voltage(V) =

$$\sqrt{\text{Rated Power(W)} \times \text{Nominal Resistance Value (ohm)}}$$

However, it shall not exceed the maximum working voltage.

## Critical Resistance Value:

The maximum nominal resistance value at which the rated power can be loaded without exceeding the maximum working voltage. The rated voltage is equal to the maximum working voltage in the critical resistance value.

## Maximum Working Value:

The maximum value of D.C. voltage or A.C. voltage (rms) capable of being applied continuously to a resistor or a resistor element. However, the maximum value of the applicable voltage is the rated voltage at the critical resistance value or lower.

## Maximum Overload Voltage:

The maximum value of voltage capable of being applied to a resistor for five seconds in the short-time overload test. Typically the applied voltage in the short-time overload test shall be 2.5 times larger than the rated voltage. However, it shall not exceed the maximum overload voltage.

## Dielectric Withstanding Voltage:

A.C. voltage (rms) that can be applied to a designated spot between the electrode and the outer coating for one minute in the dielectric withstanding voltage test.

## Rated Ambient Temperature:

The maximum ambient temperature at which a resistor is capable of being used continuously with the prescribed rated power. The rated ambient temperature refers to the temperature around the resistor inside the equipment, not to the air temperature outside the equipment.

## Derating Curve:

The curve that expresses the relation between ambient temperature and the maximum value of continuously loadable power at its temperature, which is generally expressed in percentage.

## Temperature Coefficient of Resistance (T.C.R.):

The rate of change in resistance value per 1°C in the prescribed temperature within the range of resistor operating temperature shall be expressed in the following formula:


$$\text{T.C.R. (ppm/°C)} = \frac{R - R_0}{R_0} \times \frac{1}{T - T_0} \times 10^6$$

Where: R: Measured Resistance at T°C  
 R<sub>0</sub>: Measured Resistance at T<sub>0</sub>°C  
 T: Measured Test Temperature (°C)  
 T<sub>0</sub>: Measured Base Temperature (°C)

# Environmental Applications

## RK73B, RK73H


### Surface Temperature Rise



\* 2E based on 100% Power Rating


## RK73G

### Surface Temperature Rise



## RN73/RN73H


### Surface Temperature Rise




## NV73

### Voltage Current Curves


**NV73A 1E**




**NV73A 1J**




**NV73A 2A**




**NV73B 2A**




**NV73C 2A**




**NV73A 2B**



**NV73B 2B**



**NV73B 2C**




Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

12/01/09


## NV73

### Voltage Current Curves (continued)


**NV73 2E**



**NV73 2J**




**NV73 2L**




## NVD

### Typical Characteristics (Ta = +25°C) D05U

**Voltage-Current Characteristics (NVD05S-018~NVD05U-068)**




**Image Derating (NVD05S-018~NVD05U-068)**




Surge current is related to impulse width and its repetition times.

**Voltage-Current Characteristics (NVD05U-082~NVD05U-470)**



**Image Derating (NVD05U-082~NVD05U-470)**







Surge current is related to impulse width and its repetition times.

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.






11/30/08

## NVD (continued)

### Typical Characteristics (Ta = +25°C) D07U



### Typical Characteristics (Ta = +25°C) D10U/10UB








Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

11/30/08







## NVD (continued)

### Typical Characteristics (Ta = +25°C) D14U



### Typical Characteristics (Ta = +25°C) D20U







Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.





11/30/08

## KL73

### L-Frequency Characteristics



### Q-Frequency Characteristics



Test equipment: HP4291B impedance analyzer (1E, 1J, 2A, 2B)