

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924 (ChemTel)
International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: RT-8-A RUST TREATMENT 8OZ BO
Item No: 81775
Product Type: Acid-modified emulsion

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
WATER 7732-18-5	40-50	Not listed	Not listed
VINYLDENE-ACRYLIC COPOLYMER MIXTURE	30-40	Not listed	Not listed
BARIUM SULFATE 7727-43-7	5-15	10 mg/m ³	15 mg/m ³
2-BUTOXYETHANOL 111-76-2	<3	20 ppm	50 ppm; 240 mg/m ³
PROPYLENE GLYCOL 57-55-6	<3	Not listed	Not listed
ORGANIC ACID 1401-55-4	<3	Not listed	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. May cause gastric disturbances if swallowed. Exposure to 2-butoxyethanol can cause nausea, dizziness, vomiting, malaise, incoordination, diarrhea, weakness, eye redness and swelling of conjunctiva. The organic acid can irritate the nose and throat upon inhalation. The low concentration of these components minimize the probability that these symptoms may occur..

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Overexposure may cause eye and skin redness.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
BARIUM SULFATE 7727-43-7	5-15		Group A4 - Not classifiable	
2-BUTOXYETHANOL 111-76-2	<3	male rat-no evidence; female rat-equivocal evidence; male mice- some evidence; female mice-some evidence	A3	Group 3; Monograph 88, 2006
ORGANIC ACID 1401-55-4	<3			Group 3; Suppl. 7, pg. 72, 1987; Monograph 10, 1976

**Medical Conditions Recognized as
Being Aggravated by Exposure:** May aggravate preexisting dermatitis.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): None - aqueous
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

5. FIRE FIGHTING MEASURES

Special Fire-Fighting Procedures:**Hazardous Products of Combustion:****Unusual Fire/Explosion Hazards:**

Firefighters should wear self-contained breathing apparatus.

Oxides of carbon, Hydrogen chloride, Irritating vapors

None.

Lower Explosive Limit:

1.1; 2-butoxyethanol

Upper Explosive Limit:

10.6; 2-butoxyethanol

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Residues may be cleaned up with soap and water.

7. HANDLING AND STORAGE

Storage:

Store below 100°F. Do not freeze.

Handling:

Avoid contact with skin and eyes. Do not inhale vapors. Wash thoroughly after handling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses.

Skin:

Rubber or plastic gloves.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection:

Not required under normal use. An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

White liquid

Odor:

Mild

Boiling Point:

212°F

pH:

2.05-3.05

Solubility in Water:

Soluble

Specific Gravity:

1.18-1.26

VOC(Wt.%):

2%

Vapor Pressure:

24 mm Hg

Vapor Density (Air=1):

1.2

Evaporation Rate:

<1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

Will not occur

Incompatibilities:

Avoid contact with bases and strong oxidizers

Conditions to Avoid:

Heat. Freezing.

Hazardous Products of Combustion:

Oxides of carbon, Hydrogen chloride, Irritating vapors

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:

Disposal should be made in accordance with federal, state and local regulations..

US EPA Waste Number:

D002 as per 40CFR 261.22, May be a TCLP waste per 40CFR 261.24/Barium.

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)**Ground Transport (DOT)****DOT Shipping Name:**

Not regulated

Hazard Class:

None

UN/ID Number:

None

14. TRANSPORTATION INFORMATION

IATA

Proper Shipping Name: Not regulated
Class or Division: None
UN/ID Number: None

IMDG

Proper Shipping: Not regulated
Hazard Class: None
UN Number: None

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

2-BUTOXYETHANOL, BARIUM COMPOUND

California Proposition 65: WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: February 28, 2011

Revision 2

Number:

Telephone No.: 1-87-Permatex (877) 376-2839